



Mounting: recessed into ceiling
Housing: cold rolled sheet, aluminum alloy
Reflector: aluminum
Finish options:
 01-white matte
 11-black matte

LED: COB (Citizen)
CRI: Ra>90
CCT:
 CT27-2700k
 CT30-3000k
 CT40-4000k
 CT50-5000k
 CT60-6000k

LED driver: remote
Volt AC: 220-240V
LED driver options:
 ND - non-dimmable
 PH - phase dimmable
 010V - 0-10V dimmable
 DALI - compatible
Note: *Lm given in data is based on 3000k



Areas of use:
 indoors:
 public/ private/ residential
 show-rooms
 corridors
 offices



Ref Code	Watt	mA	Lm(±)	H
16.05.001.04.13	13W	350	1300	120
16.05.001.01.18	18W	500	1900	120
16.05.001.02.26	26W	700	2700	120
16.05.001.03.33	33W	900	3400	135

Beam Angle-Code:

- 14°-BA14
- 24°-BA24
- 40°-BA40



Ref Code	Watt	mA	Lm(±)	H
16.05.002.04.26	2x13W	350	2700	120
16.05.002.01.36	2x18W	500	3600	120
16.05.002.02.54	2x26W	700	5400	120
16.05.002.03.66	2x33W	900	6800	135

Beam Angle-Code:

- 14°-BA14
- 24°-BA24
- 40°-BA40

