

Mounting: recessed into ceiling
 Housing: aluminum
 Diffuser: PMMA Lens
 Trim color options:
 01-white matte
 11-black matte
 * other RAL colors available on request



LED: COB
CRI: Ra>90 (±3000k)
CCT:
 CT27-2700k
 CT30-3000k

LED driver: remote
Volt AC: 220-240V
Frequency: 50-60Hz
LED driver options:
 ND - non-dimmable
 PH - phase dimmable
 010V - 0-10V dimmable
 DALI - compatible

Areas of use:
 indoors:
 public/private/residential
 show-rooms
 hotels
 offices



IP20




Ref Code	Watt	mA	Lm(±)
03.05.148.01.10	10W	500	680

Beam Angle-Code:

24°-BA24
 36°-BA36
 60°-BA60



IP54



Ref Code	Watt	mA	Lm(±)
03.05.149.01.10	10W	500	810


Beam Angle-Code:

24°-BA24
 38°-BA38
 60°-BA60



trimless

IP54



Ref Code	Watt	mA	Lm(±)	Beam Angle-Code:
03.05.150.01.13	13W	350	1400	15°-BA15/24°-BA24/38°-BA38/60°-BA60
03.05.150.02.18	18W	500	1900	12°-BA12/24°-BA24/40°-BA40
03.05.150.03.26	26W	700	2700	12°-BA12/24°-BA24/40°-BA40

